

# **Technical Information Sheet**

# QuickSeam<sup>™</sup> Cover Strip

Packaging	Part Number	
152 mm x 7.62 m per roll, 8 rolls per carton	W56RAC1693	
Note: includes scrubber handle and pads (quantity and type subject to chang without notice).		

## **Description**

The Elevate<sup>™</sup> QuickSeam Cover Strip is a 152 mm wide (6") semi-cured EPDM strip laminated to a QuickSeam tape. The strip is used to cover and seal butt-joined Elevate RubberCover<sup>™</sup> EPDM membranes.

## Application

QuickSeam Cover Strip can be applied in following Elevate system(s): RubberCover™ EPDM.

#### **Preparation**

The Elevate EPDM surfaces, attachment components and/or compatible mating surfaces must be prepared with QuickPrime<sup>™</sup> primer, using a QuickScrubber<sup>™</sup> tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

# **Method of Application**

Place the roll of cover strip on the membrane, positioned so it unrolls from the top of the roll (release paper will be on top) and center the cover strip over the exposed membrane edge(s). Unroll the cover strip onto the clean and primed surface. Advance the roll keeping the strip centered over the membrane edge(s) and peel the release paper as you apply the strip. Refer to the Elevate technical guidelines for specific installation instructions.

#### Coverage

In accordance with length of seam to be covered. Adjoining QuickSeam Cover Strips require an overlap of 5-25 mm and a QuickSeam Corner Flashing cover patch.





# **Characteristics**

Technical				
		EPDM Flashing	QuickSeam Tape	
•	Base	EPDM	Rubber polymers	
•	Color	Black	Black	
•	Solvents	None	None	
•	Solids	100%	98%	
•	State	Semi-cured	Cured	
•	Thickness	1.0 mm	0.9 mm	
•	Width	152 mm	156 mm	

#### **Storage**

Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

#### **Shelf Life**

12 months can be expected if stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

#### **Precautions**

Refer to Safety Data Sheet.

Note:

This document is meant only to highlight Elevate products and specifications based on latest knowledge and experience and is subject to change without notice. Above mentioned values are based on tested samples and may vary within applicable tolerances. For latest and complete product and detail information, please refer to the technical information posted on www.holcimelevate.com. Holcim Solutions and Products EMEA BV ("Holcim") takes responsibility for furnishing quality materials which meet Holcim's published product specifications. As neither Holcim itself nor its representatives practice architecture, Holcim offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. The selection of the appropriate product and its correct application is the responsibility of the customer and not of Holcim. No Holcim Representative is authorized to vary this disclaimer.

March 13, 2023

Page 2 of 2

