

# **Technical Information Sheet**



# QuickSeam<sup>™</sup> Drain Connector

Packaging	Part Number	
330 mm diam. ring - 25 pieces per carton	W56RAC1630	
320 mm x 350 mm square- 25 pieces per carton	W56RAC1635	
Note: scrubber pads and handles are not included.		

# **Description**

The Elevate<sup>™</sup> QuickSeam Drain Connector (Ring or Square) is designed for splicing prefabricated drain insert pieces with an EPDM flange onto Elevate EPDM membrane.

# **Application**

QuickSeam Drain Connector can be applied in following Elevate system(s): RubberGard™ EPDM and RubberCover™ EPDM.

## **Preparation**

The Elevate EPDM surface and the drain EPDM flange must be prepared with QuickPrime™ primer, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the tape to room temperature before use if exposed to temperatures below 15°C for prolonged periods.

### **Method of Application**

The QuickSeam Drain Connector Ring (diam. 330 mm) is used for splicing prefabricated drains with circular EPDM flanges to the EPDM membrane. The QuickSeam<sup>TM</sup> Drain Connector Square (320 mm x 350 mm) is used for splicing prefabricated drains with rectangular flanges.

#### Coverage

One piece per drain.





#### **Characteristics**

Technical			
		<b>Drain Connector Ring</b>	Drain Connector Square
•	Base	Rubber polymers	Rubber polymers
•	Color	Black	Black
•	Solvents	None	None
•	Solids	100 %	100 %
•	State	Cured	Cured
•	Thickness	$0.6 \text{ mm} \pm 0.1 \text{ mm}$	$0.6 \text{ mm} \pm 0.1 \text{ mm}$
•	Dimension(s) outside	330 mm (13")	320 mm x 350 mm (12.6" x 13.8")
•	Dimension(s) inside	140 mm (5.5")	105 mm x 138 mm (4.1" x 5.4")

# **Storage**

Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

#### **Shelf Life**

12 months can be expected if stored in above-mentioned conditions. Verify production date on each carton. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

#### **Precautions**

Refer to Safety Data Sheet.

#### Note:

This document is meant only to highlight Elevate products and specifications based on latest knowledge and experience and is subject to change without notice. Above mentioned values are based on tested samples and may vary within applicable tolerances. For latest and complete product and detail information, please refer to the technical information posted on www.holcimelevate.com. Holcim Solutions and Products EMEA BV ("Holcim") takes responsibility for furnishing quality materials which meet Holcim's published product specifications. As neither Holcim itself nor its representatives practice architecture, Holcim offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. The selection of the appropriate product and its correct application is the responsibility of the customer and not of Holcim. No Holcim Representative is authorized to vary this disclaimer.

